


The **S12** incorporates high-end LEDs, and circuit board material sealed in TecSeal to produce a tough and reliable lighting solution at an impressive price. Our low-profile design reduces the likelihood of damage and keeps this light in action for years of trouble-free performance. **See www.TecNiqInc.com for more details and a complete list of part numbers.**

S12

2.5" Low-Profile P2 Sidemarker W/Reflector



Specifications

Dimensions:	2.5" x 0.72" (see diagram)
LED's:	1 or 4 LED models
Current:	0.05A-0.07A
Connector:	PL2 - Non Polarized Connector
Mounting:	Grommet mounted into standard holes
Voltage:	9 - 14V DC
LED Colors:	Red & Amber
Light Output:	



Technical features

- ✦ Excellent UV resistance, and IP68 rated - dust & water proof
- ✦ Exceeds FMVSS 108 standards
- ✦ Energy efficient, drawing only 0.06A at 12V DC, and reliable performance over 100,000 hours
- ✦ TecSeal Urethane Potting material guarantees circuit boards
- ✦ Standard non-polarized connector

California Proposition 65

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer, birth defects or other reproductive harm.

Part Numbers	Description	Std. Pack	Connector
S12-AA00-1	2.5" Round Amber P2 rated Grommet Mount Sidemarker w/ Reflectivity	150	Fem 2 Pole
S12-AA40-1	2.5" Round Amber P2 rated 4 LED Grommet Mount Sidemarker w/ Reflectivity	150	Fem 2 Pole
S12-RR00-1	2.5" Round Red P2 rated Grommet Mount Sidemarker w/ Reflectivity	150	Fem 2 Pole
S12-RR40-1	2.5" Round Red P2 rated 4 LED Grommet Mount Sidemarker w/ Reflectivity	150	Fem 2 Pole

